Examples of Packaging



4 ft. 2-Light Fluorescent Wrap Vasque de 2 lampes fluorescentes de 1,2 m (4 pi) Alojamiento envolvente con 2 lámparas fluorescentes de 4´ (1,2 m)

Residential Application

- Clear acrylic lens
 Low profile design
 120V residential electronic ballast
 Chiffony CTA Dil salad.
- Applications résidentielles
 Lantille acrylique claire
 Conception à profit bas
- Aplicaciones residenciales

 Lente scritico claro
- Diseño de bajo perfil
 Reliast habeton seristancial de 100



#0163697



4 ft. Uses (2) 32'
15 lamps
2 Lamp
Utility
Wraparound



White enamel housing with clear prismatic lens Lift-and-shift lens allows for easy relamping

> Ballast filter prohibits radio interference













2 ft. 1 Lamp Narrow Striplight













- ENERGY STAR® Rated electronic ballant
- 5ft. cord with plug Ballast électronique classé
- Comprend (2) chaines de 25,4 cm (10 po) à crochets en S
- (10 po) à crochets en S

 Cordon électrique de 1,5 m (5 pi)
 avec fiche
- Balastra electrónica clasificada por ENERGY STAR®
- (2) Cadenas de 10° (25,4 cm) con gancho en S incluidas



- Equipped with electronic T8 120V ballast 0°F/-17°C start
 Equipé d'un démarrage de ballast T8
- Équipé d'un démarrage de ballast TB électronique de 120 volts 0°F/-17°C
 Equipado con balastra electrónica TB de 120 voltos 0°F/-17°C



- Designed for use with Energy efficier
 T8 lamps
 Conquipour l'usage avec les lampes
 efficaces d'énergie
 Diseñade para et use con las lámpa
- CGCG









